

Certified Reference Material

Certificate of Analysis

ISO
17034:2016ISO/IEC
17025:2017ISO
9001:2015

Product ID: IARM-FEINVR36-22

Product Description: Stainless Steel, Nickel Steel, Invar 36 / K93601

Revision No.: 000
Revision Date: 02/27/2023

Description and Intended Use: This Certified Reference Material is covered under the scope of accreditation to ISO 17034 by LGC Standards - Manchester, NH. As an ISO 17034 certified reference material, appropriate use of this material will fulfill the certified reference material and traceability requirements for use in ISO 17025 accredited laboratories. This CRM may come in the form of a solid disk, or chips. The intended use of this CRM may include, but is not limited to, the calibration of instruments and the validation of analytical methods.

Certified Values listed in wt.% with associated uncertainties

Al	0.0023	±0.0008	Cr	0.094	±0.004	Ni	36.0	±0.2	Sn	0.0042	±0.0007
As	0.0029	±0.0008	Cu	0.058	±0.002	P	0.0041	±0.0007	V	0.0013	±0.0005
B	0.0019	±0.0008	Mn	0.78	±0.01	S	0.0019	±0.0003			
C	0.0497	±0.0009	Mo	0.012	±0.001	Se	0.21	±0.03			
Co	0.010	0.001	N	0.0021	0.0002	Si	0.307	0.008			

Indicative Values listed in ppm

Fe	Balance	Nb	16	O	42	Pb	16	Sb	6
Ta	23	Ti	20	W	328	Zr	15		

Homogeneity and Uncertainty: "Uncertainty" values, as reported adjacent to certified concentration values, are based on a 95% Confidence Interval. These estimated uncertainties include the combined effects of method imprecision, material inhomogeneity, and any bias between methods. Homogeneity data from experimental XRF results are reflected in both the overall statistics and certified data. Homogeneity samples are selected by a systematic sampling procedure. The number of samples may be determined by equation 1, where N_{prod} is the number of units produced and N_{min} is the number of samples used for homogeneity testing. These samples are arranged in a simple randomized design such that each sample is analyzed multiple times by XRF. Homogeneity may also be determined within sample using an applied version of ASTM E826. A single factor ANOVA is used to calculate uncertainty due to inhomogeneity (U_{hom}). Uncertainty of the material is calculated by equation 2, where $H=U_{hom}$, S = Standard deviation, t = t-value at 95% CI, and n = number of observations.

$$1. N_{MIN} = \max(10, \sqrt[3]{N_{PROD}})$$

$$2. U_{CRM} = \frac{\sqrt{H^2 + S^2}}{\sqrt{n}} * t$$

Certification Laboratories: Much of the analytical work performed to assess this material has been carried out by laboratories with proven competence, as indicated by their accreditation to ISO 17025. It is an implicit requirement for this accreditation that analytical work should be performed with due traceability, via an unbroken chain of comparisons, each with stated uncertainty, to primary standards such as the mole, or to nationally- or internationally-recognised reference materials. Of the individual results herein, some have traceability (to the mole) via primary analytical methods. Some are traceable to substances of known stoichiometry. Most have traceability via commercial solutions. Furthermore, some results have additional traceability to NIST standards, as part of the analytical calibration or process control.

- Applied Technical Services - Marietta, GA
- Avon Specialty Metals Ltd - Gloucester, England
- Dirats Laboratories - Westfield, MA
- EAG Laboratories - Liverpool, NY
- Genitest Inc - Montreal, Canada
- IMR Test Labs - Lansing, NY
- Laboratory Testing, Inc. - Hatfield, PA
- LGC Standards - Manchester, NH
- Lucid Laboratories Pvt Ltd - Hyderabad, India
- Lukasiewicz Instytut Metalurgii Zelaza - Gliwice, Poland
- New Hampshire Materials Laboratory Inc - Somersworth, NH
- NSL Analytical Services - Cleveland, OH
- Scooby's Laboratory Service Pty Ltd - Benoni, South Africa
- SGS MSi - Melrose Park, IL
- Sheffield Assay Office - Sheffield, England

Instructions for Use: The test surface is on the opposite side of the labeled surface, which includes the material identification. The entire thickness of the unit is certified. However, the user is cautioned not to measure disks less than 2 mm thick when using X-ray fluorescence spectrometry. Each packaged disk has been prepared by finishing the test surface using a lathe. The user must determine the correct surface preparation procedure for each analytical technique. The user is cautioned to use care when either resurfacing the disk or performing additional polishing, as these processes may contaminate the surface. The minimum sample size for chips should be individually evaluated based on the analytical technique used; this would typically be greater than 0.1 grams. The material should be stored in a cool, dry location when not in use.

Chips are not recommended for gas analysis.

Period of Validity: The certification of this material is valid indefinitely, within the uncertainty specified, provided the material is handled and stored in accordance with the instructions stated on this certificate. The certification is nullified if the material is damaged, contaminated, otherwise modified, or used in a manner for which it was not intended.



Chuck Goudreau, Certifying Officer

February 27, 2023
Certification Date



ISO 17034 Accredited: Reference Materials
Producer, Certificate # 2848.02
ISO/IEC 17025 Accredited: Chemical
Testing, Certificate # 2848.01

Conditions of Sale and Supply: All CRMs & RMs sold are subject to applicable LGC Standard Terms and Conditions of Sale.



